Applicant: ULRIKE RELACT AL.

Serial No.: 09/221,789

Filed: December 28, 1998

Page : 2

said transparent encapsulating resin, and said resin containing said fluorescent material is of a substantially uniform thickness.—

ney's Docket No.: 12406-003001

--36. A white light emitting semiconductor component, comprising:

a semiconductor body emitting electromagnetic radiation during an operation of the semiconductor component, said semiconductor body having a semiconductor layer sequence suitable for emitting blue light;

a first electrical terminal and a second electrical terminal each electrically conductively connected to said semiconductor body; and

a luminescence conversion layer disposed directly on said semiconductor body, said electromagnetic radiation passing through said layer from one side to the other, said luminescence conversion layer containing a luminescent material, said luminescence conversion layer partially converting the blue light into yellow light, such that the semiconductor component emits white light including the blue light and the yellow light.--

--37. A light-radiating semiconductor component, comprising:

a semiconductor body emitting electromagnetic radiation during an operation of the semiconductor component, said semiconductor body having a semiconductor layer sequence suitable for emitting electromagnetic radiation of a first wavelength range selected from a spectral region consisting of ultraviolet, blue, and green;

a first electrical terminal and a second electrical terminal each electrically conductively connected to said semiconductor body;

Conti